



LEVEL CROSSINGS ACT 1983

THE NETWORK RAIL SALTCOATS LEVEL CROSSING ORDER 2024

Made on 18th June 2024

Coming into force on 1st July 2024

The Secretary of State for Transport, having been requested by Network Rail Infrastructure Ltd (“the operator”) to make an Order under section 1 of the Level Crossings Act 1983¹ (“the Act”) makes the following Order in exercise of his powers under the Act and of all other enabling powers, in accordance with the draft Order which accompanied the request subject to those modifications the Secretary of State thought fit to make.

1. This Order may be cited as the Network Rail Saltcoats Level Crossing Order 2024 and shall come into force on 1st July 2024.

Interpretation

2. In this Order:
 - a. “the operator” means Network Rail Infrastructure Ltd or any person who succeeds Network Rail Infrastructure Ltd as the person responsible for operating the level crossing;
 - b. “the local traffic authority” means Cumbria County Council or any person who succeeds Cumbria County Council;
 - c. “the specified road” means the road (including any footways) which crosses the railway at the crossing;
 - d. “the carriageway” means the carriageway of the specified road (excluding any footways);
 - e. “the crossing” means the level crossing described in Schedule 1 to this Order;
 - f. “the Regulations” means the Traffic Signs Regulations and General Directions 2016² and its successors;

¹ 1983 c.16


² (Part 1 of S.I. 2016/362)

- g. “road users” means anyone required to have regard to the Highway Code who is using the crossing, including pedestrians, mobility scooter users, cyclists, horse riders, vehicle drivers and motorcyclists;
- h. the expressions “left-hand side” and “right-hand side” means how they would appear to a person approaching the crossing along the specified road;
- i. where this Order specifies that the operator or local traffic authority must use a sign prescribed in the Regulations, if there is any amendment to the Regulations and the sign specified by this Order retains its status under the amended Regulations, its continued use is required by this Order and this Order should be read as if the amended Regulations and/or diagram number applies (if applicable).

Application

- 3. The following provisions, being provisions which in the opinion of the Secretary of State are necessary or expedient for the safety or convenience of those using the crossing, apply in respect of the crossing:
 - a. the operator shall provide, operate and maintain the protective equipment specified in Schedule 2 and Schedule 4;
 - b. the local traffic authority shall provide and maintain the protective equipment specified in Schedule 3;
 - c. the operator and local traffic authority shall observe the conditions and requirements specified in Schedule 5.
- 4. The Traffic Signs Regulations and General Directions 2016 shall apply to any traffic sign specified in this Order as they would to a traffic sign caused or permitted to be placed by a local traffic authority.

Signed by authority of the Secretary of State on 18th June 2024



Thomas Wake
Head of Mainline Inspection North, Railway Safety
Office of Rail and Road

Schedule 1 - The crossing

The level crossing known as Saltcoats, where Saltcoats is crossed by the railway between Ravenglass for Eskdale and Drigg Stations.

At Ordnance Survey National Grid Reference SD 078 972.

At Unique Street Reference Number 9201236.

Schedule 2 - Protective equipment provided by the operator

Audible Warnings

1. Audible warning devices shall be provided, suitably located and of the appropriate volume, taking account of local requirements, to warn users of the activation of the crossing.

Barriers

2. A lifting barrier shall be pivoted as close to the railway as practicable on the right-hand side of the specified road on the northern approach to the crossing and on the left-hand side of the specified road on the southern approach.
3. The barriers shall be kept fully raised except when any train crosses the specified road, or for the purpose of maintenance or testing. The electric lights on each barrier shall be lit except when the barriers are fully raised.
4. When lowered the barriers shall be as nearly horizontal as possible and shall extend across the full width of the carriageway and any footway(s).
5. When lowered, the barriers and skirts shall be of sufficient height to prevent, so far as is reasonably practicable, access to the railway, either over or under the barriers.
6. When in the fully raised position the barriers and skirts shall not obstruct or interfere with users of the crossing.
7. The barriers shall be as light as possible but shall also be strong enough to prevent foreseeable distortion or fracture likely to be caused by wind pressure.
8. The barriers shall be easily visible to road users. This shall require the use of:
 - a. alternate red and white bands to the full depth of the barriers to clearly indicate the position of the barriers to approaching road users. The bands shall be either 500 or 600 millimetres long approximately;
 - b. retro-reflective strips that are the same colour as the band on which they are placed; and
 - c. non-flashing red lights evenly placed along the length of the barrier.
9. Suitable guards or other protection shall be provided for each barrier machine to prevent danger to persons from the operating mechanism of the machine.

Carriageway and any footways

10. The carriageway and any footways over the crossing shall be wide enough to safely accommodate road users.
11. Tactile paving of a type specified in and located according to published guidance shall be provided in each footway on each approach to the crossing.

12. The surface of the carriageway and any footways over the crossing shall be maintained in a good and even condition and, with the co-operation of the local traffic authority, kept consistent with the surface of the carriageway and any footways on each approach to the crossing.

Lighting

13. Lighting shall be provided at least to the same standard as the lighting of the carriageway on the approaches to the crossing.
14. There shall be sufficient lighting at the crossing to provide a clear view of the whole crossing at the control point.
15. Sufficient lighting shall be provided for the whole crossing to be visible when under local control.

Railway signalling

16. The level crossing shall be controlled from the control point that controls the protecting signals for the crossing.
17. Visual indicators and audible alarms shall be provided at the control point to indicate the condition of the crossing.
18. Facilities shall be provided at the control point to lower and raise the barriers, release the protecting signals and stop the lowering or raising of the barriers.
19. A means of visually monitoring the crossing from the control point shall be provided.
20. Facilities shall be provided at the crossing to operate the barriers and other protective equipment under local control when required.
21. A system shall be provided to confirm that the crossing is clear of obstruction before a train is signalled over it. This system shall be signaller-operated CCTV.
22. If the system normally operates the crossing automatically, facilities shall also be provided to allow the signaller to take manual control at the control point.
23. Protecting railway signals shall be provided. These shall be interlocked with the barriers so that it shall not be possible to raise the barriers after the protecting signal has displayed a proceed aspect unless any approaching train has passed over the crossing or sufficient time has elapsed to allow a train to have come to a stand. When the barriers are raised it shall not be possible to clear those signals. Minor barrier movements caused by wind, for example, should not result in signals reverting to a restrictive aspect.
24. All protective signals mentioned above shall be provided with suitable approach locking controls.

Road Markings

25. A stop line to Diagram 1001 in the Regulations shall be provided in a suitable position on each side of the railway, from which vehicle drivers can clearly see the traffic light signals.
26. Road markings to Diagram 1012.1 in the Regulations shall be provided along the edges of the carriageway and any footways over the crossing.
27. The centre line of the carriageway shall be marked on the crossing between the stop lines with a road marking to Diagram 1004.1 in the Regulations.

Traffic signs and traffic light signals

28. Traffic light signals to Diagram 3014 in the Regulations shall be provided at each corner of the crossing, and shall be suitably located, configured and aligned to warn road users that a train is approaching. The lights of the traffic light signals shall be provided with hoods to reduce the effect of sunlight glare.
29. A traffic sign to Diagram 775 in the Regulations shall be provided beneath the traffic light signals.

Trespass prevention

30. Anti-trespass guards shall be provided adjacent to both sides of the crossing surface to deter trespass onto the railway. The guards shall extend the full distance between the fences on each side of the railway.

Schedule 3 – Protective equipment provided by the local traffic authority on the approaches to the crossing

Carriageway and any footways

31. Taking into account the applicable speed limits and road conditions, the road surface on each approach to the crossing shall be constructed and maintained to reduce the risk, so far as is reasonably practicable, of vehicle drivers losing control of their vehicles.
32. The vertical profile and surface of the carriageway and any footways approaching the crossing shall be maintained in a good and even condition.
33. The vertical profile and surface of the carriageway and any footways approaching the crossing shall, in co-operation with the operator, be kept consistent with the surface of the crossing and any footways to enable safe passage of road users over the crossing.

Road markings

34. The centre line of the carriageway shall be marked for a distance of approximately 11 metres on the northern approach to the crossing and approximately 13 metres on the southern approach, measured along the centre of the carriageway from the stop lines with road markings to Diagram 1004.1 in the Regulations.

Traffic signs

35. Traffic signs to Diagrams 770 and 773 in the Regulations (including any permitted variant) shall be provided together in a suitable position on the left-hand side of the carriageway on each approach to the crossing.

Schedule 4 – The operation of the crossing by the operator

36. The protecting signals shall be controlled from the control point.
37. Signalling controls for the level crossing shall result in the crossing being clear of road users and obstructions before a train arrives.

38. The signaller/controller shall have a clear view of the whole crossing area. If the crossing is viewed by its signaller/controller through technological means, the crossing area shall remain visible until the barriers are fully lowered, the crossing is confirmed clear and the crossing-clear control is activated.
39. The visual indicators at the control point shall show when:
 - a. standby power is in use;
 - b. all the barriers are fully raised;
 - c. all the barriers are fully lowered;
 - d. at least one of the intermittent red lights of the traffic light signals on each side of the railway is showing along the carriageway.
40. The audible alarms shall sound if:
 - a. any barrier is horizontally dislocated when in the fully lowered position;
 - b. the main power supply fails;
 - c. all the red traffic light signals facing in one direction fail.
41. Under normal operation, the crossing cycle shall be initiated by the signaller when a train is approaching. The sequence of events shall be:
 - a. the barriers shall lower either automatically or manually;
 - b. the signaller/controller shall monitor the crossing during the closure sequence and take appropriate action to ensure road users or obstructions are not struck by a lowering barrier and do not become trapped on the crossing;
 - c. the protecting signals shall only be cleared after the barriers are fully lowered and the signaller/controller has confirmed that the crossing is clear.
42. The crossing barriers shall rise automatically and simultaneously after the train has traversed the crossing unless the protecting signals have been cleared for another train.
43. If a train passes any protecting signal at danger and the barriers have not already lowered, the red lights in the traffic light signals shall immediately illuminate, bypassing the amber phase. The barriers shall not lower.

Closure sequence

44. When the 'lower' control is selected, the sequence of events to close the crossing to road users shall begin. The normal sequence shall be:
 - a. the amber lights shall immediately show and the audible warning for road users shall begin. The lights shall show for approximately 3 seconds;
 - b. immediately the amber lights are extinguished the intermittent red lights of the traffic light signals shall begin to flash and, if provided, the pedestrian light signals shall show at the same time;
 - c. not less than 4 to 6 seconds later the barriers shall begin to descend and take a further 6 to 10 seconds to reach the lowered position;
 - d. the audible warning shall stop when all the barriers are fully lowered.

Opening sequence

45. The intermittent red lights of the traffic light signals and, where provided, the pedestrian light signals, shall be extinguished before the barriers have risen to their fully raised position.
46. If any barrier fails to rise from the lowered position the intermittent red lights of the traffic light signals and, where provided, the pedestrian light signals shall continue to show.
47. Should lowering or raising take an abnormally long time an audible and visual warning shall be given at the control point.
48. The operator shall periodically monitor the duration of closures of the crossing to road traffic and shall take action to ensure that the closure times are minimised effectively.

Schedule 5 - Collaboration

Responsibility of operator

49. The operator shall have in place effective arrangements to provide the local emergency services with up-to-date information about the operational status of the crossing to enable those services to plan their response to an emergency without unexpected disruption caused by the crossing.
50. The operator shall give notice in writing to the Secretary of State as soon as the provisions of Articles 3a and 3c of the Order have been met.
51. The operator shall periodically check the legibility and visibility of traffic signs and road markings on the crossing approaches and inform the local traffic authority of any action required.

Responsibility of local traffic authority

52. The local traffic authority shall take appropriate action when informed by the operator that work is required to maintain the legibility and visibility of traffic signs, including road markings, on the crossing approaches.
53. The local traffic authority shall consult the operator before any traffic signs, including road markings, or other road equipment other than those specified in this Order are placed or caused to be placed on the road in the vicinity of the crossing.